


PRODUCT FEATURES

- Ultrafast Recovery Time
- Low Recovery Loss
- Low Forward Voltage
- Low Leakage Current
- Low Inductance Package



APPLICATIONS

- Inversion Welder
- Uninterruptible Power Supply
- Plating Power Supply
- Ultrasonic Cleaner and Welder
- Converter & Chopper
- PFC



ABSOLUTE MAXIMUM RATINGS

$T_C = 25^\circ\text{C}$ unless otherwise specified

Symbol	Parameter/Test Conditions		Values	Unit
V_R	Maximum D.C. Reverse Voltage		400	V
V_{RRM}	Maximum Repetitive Reverse Voltage			
$I_{F(AV)}$	Average Forward Current	$T_C = 110^\circ\text{C}$, Per Diode	100	A
		$T_C = 110^\circ\text{C}$, Per Module	200	
$I_{F(RMS)}$	RMS Forward Current	$T_C = 110^\circ\text{C}$, Per Diode	150	
I_{FSM}	Non Repetitive Surge Forward Current	$T_J = 45^\circ\text{C}$, $t = 10\text{ms}$, Sine, peak value	1200	
		$T_J = 45^\circ\text{C}$, $t = 8.3\text{ms}$, Sine, peak value	1310	
I^2t	For Fusing	$T_J = 45^\circ\text{C}$, $t = 10\text{ms}$, Sine, peak value	7200	A ² S
		$T_J = 45^\circ\text{C}$, $t = 8.3\text{ms}$, Sine, peak value	7122	
P_D	Power Dissipation		625	W
T_J	Junction Temperature		-40 to +150	$^\circ\text{C}$
T_{STG}	Storage Temperature Range		-40 to +125	$^\circ\text{C}$
Torque	Module to Sink	Recommended (M6)	3~4.7	Nm
	Module Electrodes	Recommended (M6)		
R_{thJC}	Junction to Case Thermal Resistance(Per Diode)		0.2	$^\circ\text{C}/\text{W}$
Weight			92	g

ELECTRICAL CHARACTERISTICS

$T_C=25^{\circ}\text{C}$ unless otherwise specified

Symbol	Parameter/Test Conditions		Min.	Typ.	Max.	Unit
I_{RM}	Maximum Reverse Leakage Current	$V_R = 400\text{V}$			0.5	mA
		$V_R = 400\text{V}, T_J = 125^{\circ}\text{C}$			10	
V_F	Forward Voltage	$I_F=100\text{A}$		1.5	2.0	V
		$I_F=100\text{A}, T_J=125^{\circ}\text{C}$		1.2		
t_{rr}	Reverse Recovery Time ($I_F = 1\text{A}, di_F/dt = -200\text{A}/\mu\text{s}, V_R = 30\text{V}$)			35		ns
t_{rr}	Reverse Recovery Time	$I_F=100\text{A}, V_R=200\text{V},$		60		ns
I_{RRM}	Maximum Reverse Recovery Current	$di_F/dt = -200\text{A}/\mu\text{s}$		9		A
t_{rr}	Reverse Recovery Time	$I_F= 100\text{A}, V_R = 200\text{V},$		85		ns
I_{RRM}	Maximum Reverse Recovery Current	$di_F/dt = -200\text{A}/\mu\text{s}, T_J=125^{\circ}\text{C}$		15		A




Figure 1. Forward Voltage Drop vs Forward Current




Figure 2. Reverse Recovery Time vs di_F/dt




Figure 3. Reverse Recovery Current vs di_F/dt




Figure 4. Reverse Recovery Charge vs di_F/dt




Figure 5. Forward current vs Case temperature





Figure 6. Transient Thermal Impedance



Dimensions in (mm)
Figure 7. Package Outline